

SMD LED LAMP

BL-LS0603XX

■ Features:

- 1.6mmx0.8mm SMD, 0.8mm THICKNESS
- Mono-color type
- Compatible with automatic placement equipment
- WIDE VIEWING ANGLE.
- IDEAL FOR BACKLIGHT AND INDICATOR.
- PACKAGE: 4KPCS/REEL
- RoHs Compliance



■ Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part Number	Chip			Lens Type	Forward Voltage(VF) Unit:V		Luminous Intensity (Iv) Unit:mcd		Viewing Angle 2θ1/2 (deg)
	Emitted Color	Material	λ _P (nm)						
					Typ	Max	Min.	Typ.	
BL-LS0603HC	Red	GaP	700	Water Clear	2.2	2.7	0.3	1.0	130
BL-LS0603SRC	Super Red	AlGaAs	660		1.85	2.30	5	13	
BL-LS0603LRC	Super Red	AlGaAs	660		1.85	2.30	10	28	
BL-LS0603URC	Ultra Red	AlGaAs	660		1.95	2.50	20	45	
BL-LS0603EC	Orange	GaAsP	640		2.10	2.70	1	6	
BL-LS0603YC	Yellow	GaAsP	583		2.15	2.70	1	6	
BL-LS0603GC	Green	GaP	568		2.30	2.70	6	15	

■ Absolute maximum ratings (Ta=25°C)

Parameter	H	SR	LR	UR	E	Y	G	Unit
Forward Current I_F	30	30	30	30	30	30	30	mA
Power Dissipation P_d	65	78	78	78	65	65	65	mW
Reverse Voltage V_R	5	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	100	100	100	100	100	100	100	mA
Operation Temperature T_{OPR}	-30 to +80							°C
Storage Temperature T_{STG}	-40 to +85							°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)							°C

SMD LED LAMP

BL-LS0603XX

■ Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part Number	Chip			Lens Type	Forward Voltage(VF) Unit:V		Luminous Intensity (Iv) Unit:mcd		Viewing Angle 2θ1/2 (deg)
	Emitted Color	Material	λ _P (nm)						
					Typ	Max	Min.	Typ.	
BL-LS0603UDR	Ultra Red	AlGaAs	655	Water Clear	2.10	2.50	22	55	130
BL-LS0603UHR	Ultra Red	AlGaAs	645		2.10	2.60	30	80	
BL-LS0603UEC	Ultra Orange	AlGaAs	630		2.10	2.50	30	80	
BL-LS0603UHD	Ultra Orange	AlGaAs	618		2.10	2.60	50	110	
BL-LS0603UYO	Ultra Amber	AlGaInP	610		2.10	2.60	30	80	
BL-LS0603UYC	Ultra Yellow	AlGaInP	593		2.10	2.60	25	70	
BL-LS0603UGC	Ultra Green	AlGaInP	575		2.20	2.70	10	40	
BL-LS0603PGC	Ultra Pure Green	InGaN	525		3.50	4.20	50	100	
BL-LS0603BGC	Ultra Bluish Green	InGaN	505		3.50	4.20	50	110	
BL-LS0603DNB	Blue	InGaN	470		3.50	4.20	10	33	
BL-LS0603UBC	Ultra Blue	InGaN	470		3.50	4.20	10	30	
BL-LS0603UWC	Ultra White	InGaN	/		3.50	4.20	40	200	

■ Absolute maximum ratings (Ta=25°C)


Parameter	UDR	UHR	UE	UHD	UYO	UY	UG	PG	BG	DNB	UB	UW	Unit
Forward Current I_F	30	30	30	30	30	30	30	30	30	30	30	30	mA
Power Dissipation P_d	78	78	78	78	78	78	78	78	78	78	78	78	mW
Reverse Voltage V_R	5	5	5	5	5	5	5	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	100	100	100	100	100	100	100	100	100	100	100	100	mA
Operation Temperature T_{OPR}	-30 to +80												°C
Storage Temperature T_{STG}	-40 to +85												°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)												°C

SMD LED LAMP


BL-LS0603XX

■ Package configuration & Internal circuit diagram

BL-LS0603 Series Package Outline Drawing



Recommended Soldering Pad Dimensions



Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is $\pm 0.25(0.01)$ unless otherwise noted.
3. Specifications are subject to change without notice.




SMD LED LAMP

BL-LS0603XX

■ Tape Specifications

Unit: mm


Tolerance: ± 0.1









SMD LED LAMP

BL-LS0603XX

Typical electrical-optical characteristics curves:



- | | |
|---|--------------------------------------|
| (1) - GaAsP/GaAs 655nm/Red | (9) - GaAlAs 880nm |
| (2) - GaP 570nm/Yellow Green | (10) - GaAs/GaAs & GaAlAs/GaAs 940nm |
| (3) - GaAsP/GaP 585nm/Yellow | (A) - GaN/SiC 430nm/Blue |
| (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red | (B) - InGaN/SiC 470nm/Blue |
| (5) - GaP 700nm/Bright Red | (C) - InGaN/SiC 505nm/Ultra Green |
| (6) - GaAlAs/GaAs 660nm/Super Red | (D) - InGaAl/SiC 525nm/Ultra Green |
| (8) - GaAsP/GaP 610nm/Super Red | |



NOTE: 25°C free air temperature unless otherwise specified